



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BRT WH P BASE EXT LTX 5GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24001      01      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22		68	1% - 5%
QUARTZ	14808-60-7				.12
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/gl ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:  
No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BRT WH P BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BRT WH P BASE EXT LTX GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24002      02      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22		68	1% - 5%
QUARTZ	14808-60-7				.12
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BRT WH P BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BRT WH P BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BRT WH P BASE EXT LTX QT      HMIS CODES: H F R P  
PRODUCT CODE: .24003      03      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.12
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BRT WH P BASE EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:  
No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BRT WH P BASE EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BRT WH P BASE EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ADOBE BEIGE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P ADOBE BEIGE EXT LTX 5GAL HMIS CODES: H F R P  
PRODUCT CODE: .24011 01 1 0 0

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY

ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116

EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016

INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15

NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

=====**SECTION II - INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
IRON OXIDE YELLOW	51274-00-1			1%	5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS (REC): 5 mg/m3					
QUARTZ	14808-60-7				.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.26  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.41 lb/gl ,49 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

## **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P ADOBE BEIGE EXT LTX GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24012      02      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22		68	1% - 5%
IRON OXIDE YELLOW	51274-00-1				1% - 5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS (REC): 5 mg/m3					
QUARTZ	14808-60-7				.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.26  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.41 lb/gl ,49 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

## **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ADOBE BEIGE EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## SECTION VIII - CONTROL MEASURES

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ADOBE BEIGE EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P TINT BASE EXT LTX 5GAL HMIS CODES: H F R P  
PRODUCT CODE: .24101 01 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT PERCENT
		mm Hg @	TEMP	
TALC [Silicates] (Respirable Dust)	14807-96-6			5% - 10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3				
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1% - 5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3				
PROPYLENE GLYCOL	57-55-6	.22	68	1% - 5%
QUARTZ	14808-60-7			.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m				

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:  
No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TINT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P TINT BASE EXT LTX GAL HMIS CODES: H F R P  
PRODUCT CODE: .24102 02 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
TALC [Silicates] (Respirable Dust)	14807-96-6			5% - 10%	
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1% - 5%	
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1% - 5%	
QUARTZ	14808-60-7			.16	
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:  
No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TINT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P TINT BASE EXT LTX QT HMIS CODES: H F R P  
PRODUCT CODE: .24103 03 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TINT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TINT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P FRENCH GRAY EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P FRENCH GRAY EXT LTX 5GAL HMIS CODES: H F R P  
PRODUCT CODE: .24131 01 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT PERCENT
		mm Hg @	TEMP	
TALC [Silicates] (Respirable Dust)	14807-96-6			5% - 10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3				
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1% - 5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 10 mg/m3				
PROPYLENE GLYCOL	57-55-6	.22	68	1% - 5%
QUARTZ	14808-60-7			.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m				

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/gl ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P FRENCH GRAY EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P FRENCH GRAY EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P FRENCH GRAY EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P FRENCH GRAY EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P FRENCH GRAY EXT LTX GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24132      02      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.25  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.42 lb/gal ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/gal ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P FRENCH GRAY EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P FRENCH GRAY EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P FRENCH GRAY EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== **SECTION IX - DISCLAIMER** =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P PONCHO TAN EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P PONCHO TAN EXT LTX GAL HMIS CODES: H F R P  
PRODUCT CODE: .24182 02 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
NATURAL DIATOMACEOUS EARTH AMORPHOUS SILICA (Total Dust)	61790-53-2			1%	5%
OSHA TWA: 6 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 10 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
IRON OXIDE YELLOW	51274-00-1			1%	5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS (REC): 5 mg/m3					
QUARTZ	14808-60-7				.16
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.26  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.41 lb/gl ,49 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,20 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P PONCHO TAN EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

## **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P PONCHO TAN EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P PONCHO TAN EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BARN RED EXT LTX GAL HMIS CODES: H F R P  
PRODUCT CODE: .24312 02 1 0 0

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

**MANUFACTURER'S NAME:** DAVIS PAINT COMPANY  
**ADDRESS :** 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
**EMERGENCY PHONE :** (816)-471-4447 **DATE PRINTED :** 1/12/2016  
**INFORMATION PHONE :** (816)-471-4447 **DATE REVISED :** 05/19/15  
**NAME OF PREPARER :** Bob Willhite

**FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053**

=====**SECTION II - INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
CALCIUM CARBONATE (Total Dust)	1317-65-3			20%	25%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 5 mg/m3					
IRON OXIDE (Total Dust)	1309-37-1			5%	10%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS (REC): 5 mg/m3					
MICA [Silicates] (Respirable Dust)	12001-26-2			1%	5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.15
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					
CARBON BLACK	1333-86-4				.14
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS (REC): 3.5 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

**BOILING RANGE:** 365 **SPECIFIC GRAVITY (H2O=1):** 1.36  
**VAPOR DENSITY: HEAVIER THAN AIR** **EVAPORATION RATE: SLOWER THAN ETHER**  
**COATING V.O.C.:** 0.4 lb/gl ,48 g/l  
**MATERIAL V.O.C.:** 0.17 lb/gl ,21 g/l  
**SOLUBILITY IN WATER:** Complete  
**APPEARANCE AND ODOR:** Liquid, mild odor

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

**FLASH POINT (TCC):** 218 deg F(Theoretical, by lowest flashing solvent).  
**FLASH POINT (TCC):** 200+ deg F(Actual). Does not exhibit flash.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

**FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5**

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

### **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

### **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BARN RED EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## SECTION VIII - CONTROL MEASURES

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BARN RED EXT LTX QT HMIS CODES: H F R P  
PRODUCT CODE: .24313 03 1 0 0

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

**MANUFACTURER'S NAME:** DAVIS PAINT COMPANY  
**ADDRESS :** 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
**EMERGENCY PHONE :** (816)-471-4447 **DATE PRINTED :** 1/12/2016  
**INFORMATION PHONE :** (816)-471-4447 **DATE REVISED :** 05/19/15  
**NAME OF PREPARER :** Bob Willhite

**FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053**

=====**SECTION II - INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
CALCIUM CARBONATE (Total Dust)	1317-65-3			20% - 25%	
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 5 mg/m3					
IRON OXIDE (Total Dust)	1309-37-1			5% - 10%	
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS (REC): 5 mg/m3					
MICA [Silicates] (Respirable Dust)	12001-26-2			1% - 5%	
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1% - 5%	
QUARTZ	14808-60-7			.15	
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					
CARBON BLACK	1333-86-4			.14	
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS (REC): 3.5 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

**BOILING RANGE:** 365 **SPECIFIC GRAVITY (H2O=1):** 1.36  
**VAPOR DENSITY: HEAVIER THAN AIR** **EVAPORATION RATE: SLOWER THAN ETHER**  
**COATING V.O.C.:** 0.4 lb/gl ,48 g/l  
**MATERIAL V.O.C.:** 0.17 lb/gl ,21 g/l  
**SOLUBILITY IN WATER:** Complete  
**APPEARANCE AND ODOR:** Liquid, mild odor

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

**FLASH POINT (TCC):** 218 deg F(Theoretical, by lowest flashing solvent).  
**FLASH POINT (TCC):** 200+ deg F(Actual). Does not exhibit flash.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

**FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5**

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

### **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

### **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BARN RED EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

---

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== **SECTION IX - DISCLAIMER** =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TIMBER BROWN EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P TIMBER BROWN EXT LTX GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24372      02      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
CALCIUM CARBONATE (Total Dust)	1317-65-3		15% - 20%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3			
TALC [Silicates] (Respirable Dust)	14807-96-6		10% - 15%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3			
IRON OXIDE (Total Dust)	1309-37-1		1% - 5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS(REC): 5 mg/m3			
IRON OXIDE YELLOW	51274-00-1		1% - 5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS(REC): 5 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68    1% - 5%
CARBON BLACK	1333-86-4		.82
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS(REC): 3.5 mg/m			
QUARTZ	14808-60-7		.29
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m			

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.32  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.4 lb/gl ,48 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,21 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TIMBER BROWN EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TIMBER BROWN EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TIMBER BROWN EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

## PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TIMBER BROWN EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P TIMBER BROWN EXT LTX QT      HMIS CODES: H F R P  
PRODUCT CODE: .24373      03      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
CALCIUM CARBONATE (Total Dust)	1317-65-3			15%	20%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			10%	15%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
IRON OXIDE (Total Dust)	1309-37-1			1%	5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS(REC): 5 mg/m3					
IRON OXIDE YELLOW	51274-00-1			1%	5%
OSHA TWA: 10 mg/m3, ACGIH TLV: 5 mg/m3, DAVIS(REC): 5 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
CARBON BLACK	1333-86-4				.82
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS(REC): 3.5 mg/m					
QUARTZ	14808-60-7				.29
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.32  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.4 lb/gl ,48 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,21 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P TIMBER BROWN EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

### SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TIMBER BROWN EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P TIMBER BROWN EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

## PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BLACK EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BLACK EXT LTX GAL HMIS CODES: H F R P  
PRODUCT CODE: .24382 02 1 0 0

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

**MANUFACTURER'S NAME:** DAVIS PAINT COMPANY  
**ADDRESS :** 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
**EMERGENCY PHONE :** (816)-471-4447 **DATE PRINTED :** 1/12/2016  
**INFORMATION PHONE :** (816)-471-4447 **DATE REVISED :** 05/19/15  
**NAME OF PREPARER :** Bob Willhite

**FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053**

=====**SECTION II - INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP		PERCENT	
CALCIUM CARBONATE (Total Dust)	1317-65-3			15% - 20%	
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			5% - 10%	
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1% - 5%	
CARBON BLACK	1333-86-4			1.37	
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS(REC): 3.5 mg/m					
QUARTZ	14808-60-7			.27	
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

**BOILING RANGE:** 365 **SPECIFIC GRAVITY (H2O=1):** 1.28  
**VAPOR DENSITY: HEAVIER THAN AIR** **EVAPORATION RATE: SLOWER THAN ETHER**  
**COATING V.O.C.:** 0.41 lb/g1 ,50 g/l  
**MATERIAL V.O.C.:** 0.17 lb/g1 ,21 g/l  
**SOLUBILITY IN WATER:** Complete  
**APPEARANCE AND ODOR:** Liquid, mild odor

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

**FLASH POINT (TCC):** 218 deg F(Theoretical, by lowest flashing solvent).  
**FLASH POINT (TCC):** 200+ deg F(Actual). Does not exhibit flash.

**FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5**



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BLACK EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

**STABILITY: STABLE**

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BLACK EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BLACK

EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== **SECTION IX - DISCLAIMER** =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BLACK EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P BLACK EXT LTX QT HMIS CODES: H F R P  
PRODUCT CODE: .24383 03 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
CALCIUM CARBONATE (Total Dust)	1317-65-3			15%	20%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
CARBON BLACK	1333-86-4				1.37
OSHA TWA: 3.5 mg/m3, ACGIH TLV: 3.5 mg/m3, DAVIS(REC): 3.5 mg/m					
QUARTZ	14808-60-7				.27
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.28  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.41 lb/g1 ,50 g/l  
MATERIAL V.O.C.: 0.17 lb/g1 ,21 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P BLACK EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

## **SPECIAL FIREFIGHTING PROCEDURES**

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## **UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

### **CONDITIONS TO AVOID**

Excessive heat, poor ventilation, excessive aging.

### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### **HAZARDOUS POLYMERIZATION:**

Will not occur under normal conditions

## ===== SECTION VI - HEALTH HAZARD DATA =====

### **INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### **SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### **SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

No adverse effects from available information.

### **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation.

### **HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:**

No

This product contains carbon black which has been identified as possibly carcinogenic to humans (IARC Group 2B - Based on sufficient evidence for carcinogenicity in laboratory animal studies, but inadequate evidence for cancer in exposed humans). Normal application procedures pose minimal hazard since the carbon black is wet and encapsulated. Risk of cancer may be reduced by following recommended ventilation/control practices, keeping below TWA and/or TLV values listed



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BLACK EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

in section 2. This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P BLACK

EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

---

## EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== **SECTION IX - DISCLAIMER** =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX 5GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24751      01      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 02/18/14  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
NEPHELINE SYENITE	37244-96-5		5% - 10%
OSHA PEL: N/A      ACGIH TLV: 10mg/m3      DAVIS (REC): 5mg/m3			
MICA [Silicates] (Respirable Dust)	12001-26-2		1% - 5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68      1% - 5%

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.2  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.7 lb/gl ,84 g/l  
MATERIAL V.O.C.: 0.25 lb/gl ,30 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:  
No

N/A

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

### EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

**WASTE DISPOSAL METHOD**

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

**VENTILATION**

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

**PROTECTIVE GLOVES**

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

**EYE PROTECTION**

Use chemical safety glasses or goggles (ANSI 287.1-1968).

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

**WORK/HYGIENIC PRACTICES**

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

---

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX GAL      HMIS CODES: H F R P  
PRODUCT CODE: .24752      02      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 02/18/14  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT	PERCENT	
NEPHELINE SYENITE	37244-96-5			5%	10%
OSHA PEL: N/A      ACGIH TLV: 10mg/m3      DAVIS (REC): 5mg/m3					
MICA [Silicates] (Respirable Dust)	12001-26-2			1%	5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.2  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.7 lb/gl ,84 g/l  
MATERIAL V.O.C.: 0.25 lb/gl ,30 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES  
None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:  
No

N/A

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

### EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## SECTION VIII - CONTROL MEASURES

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

### WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## SECTION IX - DISCLAIMER



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

---

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX QT      HMIS CODES: H F R P  
PRODUCT CODE: .24753      03      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 02/18/14  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
NEPHELINE SYENITE	37244-96-5		5% - 10%
OSHA PEL: N/A      ACGIH TLV: 10mg/m3      DAVIS (REC): 5mg/m3			
MICA [Silicates] (Respirable Dust)	12001-26-2		1% - 5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68      1% - 5%

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.2  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.7 lb/gl      ,84 g/l  
MATERIAL V.O.C.: 0.25 lb/gl      ,30 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:  
No

N/A

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

### EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

**WASTE DISPOSAL METHOD**

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

**VENTILATION**

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

**PROTECTIVE GLOVES**

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

**EYE PROTECTION**

Use chemical safety glasses or goggles (ANSI 287.1-1968).

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

**WORK/HYGIENIC PRACTICES**

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====



## MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

---

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ACCENT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P ACCENT BASE EXT LTX 5GAL HMIS CODES: H F R P  
PRODUCT CODE: .24991 01 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
CALCIUM CARBONATE (Total Dust)	1317-65-3			20%	25%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.29
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.31  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.4 lb/gl ,48 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,21 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== **SECTION IX - DISCLAIMER** =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P ACCENT BASE EXT LTX GAL HMIS CODES: H F R P  
PRODUCT CODE: .24992 02 1 0 0

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY

ADDRESS : 1311 IRON STREET  
P.O. BOX 7589  
N. KANSAS CITY, MO 64116

EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016

INFORMATION PHONE : (816)-471-4447 DATE REVISED : 05/19/15

NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

=====**SECTION II - INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
CALCIUM CARBONATE (Total Dust)	1317-65-3			20%	25%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS(REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS(REC): 2 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.29
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS(REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: 365

SPECIFIC GRAVITY (H2O=1): 1.31

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 0.4 lb/gl ,48 g/l

MATERIAL V.O.C.: 0.17 lb/gl ,21 g/l

SOLUBILITY IN WATER: Complete

APPEARANCE AND ODOR: Liquid, mild odor

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).

FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ACCENT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:  
No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

---

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ACCENT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG LATEX H/P ACCENT BASE EXT LTX QT      HMIS CODES: H F R P  
PRODUCT CODE: .24993      03      1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY  
ADDRESS : 1311 IRON STREET  
          P.O. BOX 7589  
          N. KANSAS CITY, MO 64116  
EMERGENCY PHONE : (816)-471-4447      DATE PRINTED : 1/12/2016  
INFORMATION PHONE : (816)-471-4447      DATE REVISED : 05/19/15  
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT  
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT	
		mm Hg @ TEMP	PERCENT		
CALCIUM CARBONATE (Total Dust)	1317-65-3			20%	25%
OSHA TWA: 15 mg/m3, ACGIH TLV: 10 mg/m3, DAVIS (REC): 5 mg/m3					
TALC [Silicates] (Respirable Dust)	14807-96-6			5%	10%
OSHA TWA: 20 mppcf, ACGIH TLV: 2 mg/m3, DAVIS (REC): 2 mg/m3					
PROPYLENE GLYCOL	57-55-6	.22	68	1%	5%
QUARTZ	14808-60-7				.29
OSHA TWA: 0.1 mg/m3, ACGIH TLV: 0.1 mg/m3, DAVIS (REC): 0.1 mg/m					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365      SPECIFIC GRAVITY (H2O=1): 1.31  
VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 0.4 lb/gl ,48 g/l  
MATERIAL V.O.C.: 0.17 lb/gl ,21 g/l  
SOLUBILITY IN WATER: Complete  
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).  
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6      UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

## SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

## SECTION V - REACTIVITY DATA

### STABILITY: STABLE

### CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

### INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

### HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

## SECTION VI - HEALTH HAZARD DATA

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

**CARCINOGENICITY:** NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED:

No

This product contains quartz which has been identified by the IARC as a Class 1 carcinogen. This is a naturally occurring impurity of calcium carbonate (chalk) or magnesium silicate (talc). Normal application procedures pose minimal hazard since the quartz is wet and encapsulated. Risk of cancer depends on the level and duration of sanding or abrading dried paint films. Stay below TWA and/or TLV values listed in section 2, using NIOSH-approved dust filter respirators.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG LATEX H/P ACCENT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

---

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

## EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

### WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

### OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

### VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

### PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

### EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.



# MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY  
GG LATEX H/P ACCENT BASE EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

## WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

## ===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.