



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX 5GAL HMIS CODES: H F R P
PRODUCT CODE: .24751 01 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY
ADDRESS : 1311 IRON STREET
 P.O. BOX 7589
 N. KANSAS CITY, MO 64116
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 02/18/14
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
NEPHELINE SYENITE	37244-96-5		5% - 10%
OSHA PEL: N/A ACGIH TLV: 10mg/m3 DAVIS (REC): 5mg/m3			
MICA [Silicates] (Respirable Dust)	12001-26-2		1% - 5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68 1% - 5%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.2
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 0.7 lb/gl ,84 g/l
MATERIAL V.O.C.: 0.25 lb/gl ,30 g/l
SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:
No

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX 5GAL

Date Printed: 1/12/2016

Page 4 of 4

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX GAL HMIS CODES: H F R P
PRODUCT CODE: .24752 02 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY
ADDRESS : 1311 IRON STREET
 P.O. BOX 7589
 N. KANSAS CITY, MO 64116
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 02/18/14
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
NEPHELINE SYENITE	37244-96-5		5% - 10%
OSHA PEL: N/A ACGIH TLV: 10mg/m3 DAVIS (REC): 5mg/m3			
MICA [Silicates] (Respirable Dust)	12001-26-2		1% - 5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68 1% - 5%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.2
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 0.7 lb/gl ,84 g/l
MATERIAL V.O.C.: 0.25 lb/gl ,30 g/l
SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:
No

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX GAL

Date Printed: 1/12/2016

Page 4 of 4

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 1 of 4

PRODUCT NAME: GG EXTERIOR LATEX PRIMER EXT LTX QT HMIS CODES: H F R P
PRODUCT CODE: .24753 03 1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DAVIS PAINT COMPANY
ADDRESS : 1311 IRON STREET
 P.O. BOX 7589
 N. KANSAS CITY, MO 64116
EMERGENCY PHONE : (816)-471-4447 DATE PRINTED : 1/12/2016
INFORMATION PHONE : (816)-471-4447 DATE REVISED : 02/18/14
NAME OF PREPARER : Bob Willhite

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT - CONTACT
INFOTRAC PHONE: (800)-535-5053

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		mm Hg @ TEMP	PERCENT
NEPHELINE SYENITE	37244-96-5		5% - 10%
OSHA PEL: N/A ACGIH TLV: 10mg/m3 DAVIS (REC): 5mg/m3			
MICA [Silicates] (Respirable Dust)	12001-26-2		1% - 5%
OSHA TWA: 20 mppcf, ACGIH TLV: 3 mg/m3, DAVIS (REC): 3 mg/m3			
PROPYLENE GLYCOL	57-55-6	.22	68 1% - 5%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

This material may contain ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986".

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 365 SPECIFIC GRAVITY (H2O=1): 1.2
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 0.7 lb/gl ,84 g/l
MATERIAL V.O.C.: 0.25 lb/gl ,30 g/l
SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Liquid, mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (TCC): 218 deg F(Theoretical, by lowest flashing solvent).
FLASH POINT (TCC): 200+ deg F(Actual). Does not exhibit flash.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6 UPPER: 12.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

None known. However, fire fighters should wear self contained breathing apparatus to avoid inhalation if material is



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY
GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 2 of 4

involved in a general fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product. Dried finish can burn, giving off oxides of carbon.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat, poor ventilation, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin Contact: Irritating to the skin on repeated or prolonged contact. Eye Contact: Direct contact may cause eye irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

No adverse effects from available information.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute effects are listed above. No known chronic effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:
No

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Preexisting eye, skin and respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 3 of 4

clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and add absorbant earth, sand or sawdust to spilled liquid. Keep out of sewers.

WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed when not in use. Store in cool well ventilated areas away from heat and out of direct sunlight. KEEP FROM FREEZING!!! Wash thoroughly after handling.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits. Observe OSHA Standard 29CFR 1910.134.

VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29 CFR 1910.94.

PROTECTIVE GLOVES

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

EYE PROTECTION

Use chemical safety glasses or goggles (ANSI 287.1-1968).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact with contaminated clothing.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====



MATERIAL SAFETY DATA SHEET

DAVIS PAINT COMPANY

GG EXTERIOR LATEX PRIMER EXT LTX QT

Date Printed: 1/12/2016

Page 4 of 4

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. Davis Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.