



# <sup>®</sup> 250 CFM/5.5 Sones @ 0.10" SP. Horizontal CERTIFIED 260 CFM/6.0 Sones @ 0.10" SP. Vertical

## • Dimensions

Overall bottom projection - 18%" Overall top projection -12" Height - 6" Available widths: 30" & 36"

## Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel. Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

#### Motor

Fully enclosed PSC 4 pole motor. Variable speed, thermally protected, permanently lubricated. Rated 115/120 Volts, 60 hz.

## • Lighting


Enclosed in a polycarbonate lens, 60 watt max. type A15 appliance lamp (bulb not included), complete with night light setting.


## • Ducting Options

Horizontal ducting: 3<sup>1</sup>/<sub>4</sub>"x10" (duct adapter and damper included). Vertical ducting: 3<sup>1</sup>/<sub>4</sub>"x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

#### • Blade

Polymeric axial fan blade 91/8" diameter with 7 paddles.





# <u>Electrical connection</u>

Hood top - %'' knockout hole for use with %'' cable clamp Hood back - %'' knockout hole for use with %'' cable clamp

#### • Filters

UL rated, class 2 filter. Grease Filter: GF-06 (included). Charcoal Filter: CF-06 (not included).

# Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

EXPANDED PERFORMANCE												
	Static Pressure (inches of w.g.)								Sones	Fan Speed	Maximum	
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	0.3	0.35	@ .1 SP	RPM	Fan Watts	Amps
Vert Ducting High	294	279	260	250	238	213	184	151	6.0	2255	94	2.0
Horz Ducting High	292	274	250	238	225	195	165	135	5.5	2141	93	2.0
Vert Ducting Min	206	184	149	127	103	48	-	-	1.5	1579	32	
Horz Ducting Min	209	179	138	115	92	47	-	-	1.5	1499	32	

