



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/28/05

DAP® Bondex® Liquid Cement Crack Filler

- Repairs cracks and surface defects in concrete
- Self-leveling
- Easy to use, ready-mixed formula

Packaging: Quart
Color: Light Grey
UPC No: 37584

Company Identification:

Manufacturer: DAP Inc.
Marketed by: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Bondex® Liquid Cement Crack Filler is an easy-to-use, ready mixed product for the repair of horizontal concrete cracks. Repairs are ready for traffic 30 minutes following application, when directions are properly followed. Liquid Cement is self-leveling and dries gray to match most existing concrete.

Surface Preparation & Application

- Do not use if temperature is below 45°F (7°C), or if rain is likely. Keep product from freezing. Always wear rubber gloves and eye protection.
- Clean all dirt and loose debris from crack Liquid Cement must be applied to a solid, dirt-free surface.
- Shake Liquid Cement bottle prior to opening and before each use to ensure consistent mixture. Bottle nozzle should be snipped with scissors to initially open. (The product will flow faster if the bottle is set into hot water for 10 minutes prior to use in cooler temperature conditions).
- Fill crack in 3 inch layers allowing at least 24 hours between applications.
- For very thin cracks, Liquid Cement may be “pressed” or troweled flat into and around crack.

Physical & Chemical Characteristics:

Color:	Light Gray
Consistency:	Liquid
Drying time:	24 hours
Storage:	Protect from freezing. Keep out of reach of children.
Shelf Life:	1 year

Temperature
MSDS No:
Packaging:

Apply in temperatures above 40°F
000 79302 001

<u>UPC</u>	<u>Size</u>
37584	Quart

Clean Up:

Clean up with soap and water. Cured material must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.