



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 9/16/2015

## DAP® Wall Repair Patch Kit with DRYDex® Spackling

- For the quick and easy repair of holes and cracks.
- Includes all the necessary tools.
- Unique Dry Time Indicator Spackling eliminates errors.
- Repairs holes up to 4" in diameter.
- Interior

**Packaging:** Clamshell  
**Color:** Applies pink and dries white  
**UPC Numbers:** 7079812341

### Company Identification:

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224  
**Usage Information:** DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
**Order Information:** 800-327-3339  
**Fax Number:** 410-534-2650  
Also, visit the DAP website at **dap.com**.

### Product Description:

DAP® Wall Repair Patch Kit featuring DRYDex® Dry Time Indicator Spackling comes with all of the tools needed to complete a wall-patching project. This kit may be used to repair holes up to 4 inches in diameter in drywall or plaster surfaces. DRYDex® Spackling provides a unique dry-time indicator that verifies when the patched surface is ready to be sanded and painted.

#### **TOOLS INCLUDED:**

- 1 – 8 Fl. Oz. tub of DRYDex® Spackling
- 1 - 5" x 5" Fiber Tough™ patch
- 1- 4" x 3" 100 grit sand paper
- 1- 2" ergonomic plastic putty knife

### Suggested Uses:

Ideal for filling holes, cracks and defects on:

- Drywall
- Plaster

### Surface Preparation & Application:

- Make sure the area to be repaired is clean, dry, firm and free of any loose debris or materials.
- Using enclosed putty knife, apply the DRYDex® Spackling to the back of the patch. If necessary, this patch can be cut with a regular pair of scissors to fit smaller holes or cracks. Press the patch against the surface to be repair. Press firmly around the outer edges of the patch to ensure a strong bond.

- Using the enclosed putty knife, spread the DRYDex<sup>®</sup> Spackling over the patch and adjacent area. Make sure to feather edge the patch.
- Spackling compound will change color to white when the surface is ready to be sanded & painted. Apply a second finishing coat if necessary following the instruction above.
- Paint the patch surface as desired.

***NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use.***

***For Best Results:***

- Do not apply when temperatures are below 50°F.
- Do not apply outside.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- Do not use for tuck pointing applications on brick

**Physical & Chemical Characteristics:**

Consistency:	Paste
Vehicle:	Latex Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight/Gallon:	15.6
Solids:	77% by weight
Application Temperature:	50° F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint
MSDS No.:	00010420001

**Clean Up:**

Wash tools immediately after use with water. Be sure container lid is closed and tightly sealed. Store in a cool, dry place.

**Safety:**

See product label and Safety Data Sheet (SDS) for safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling 1-888-DAP-TIPS.

**Satisfaction Guaranteed:**

If product fails to perform as directed, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund within one year after purchase. DAP will not be responsible for incidental or consequential damages.