



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/30/15

DAP® KWIK SEAL ULTRA™ Premium Siliconized Sealant – Clear

- Easy clean
- Repels water, dirt & stains
- Stain proof protection
- Lifetime mold & mildew resistance guarantee
- Sealant stays looking clean, fresh & new
- 100% waterproof
- Crack proof
- Safe for granite & marble
- Water ready in 4 hours
- Easy water cleanup & low odor
- Interior

Packaging: 5.5 fluid ounces (162 mL) and 10.1 fluid ounces (300 mL)

Color: Clear

UPC Numbers: 0 70798 18895, 0 70798 18898, 0 7079818916

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also, visit the DAP website at www.dap.com

Product Description:

DAP® KWIK SEAL ULTRA™ is a high performance, premium siliconized kitchen and bath sealant that repels water, stains and dirt so the sealant stays looking clean, fresh and new. It has stain proof protection and is guaranteed to stay mold and mildew free for the life of the sealant. It can be exposed to water in as little as 4 hours after application without washing out, putting the area in service sooner. KWIK SEAL ULTRA™ is 100% waterproof and crack proof, applies easily and smoothly, is low in odor, safe for granite and marble and cleans up water. Interior use.

Suggested Uses:

Ideal for sealing:

- Tubs
- Sinks
- Backsplashes
- Showers
- Countertops
- Toilets
- Fixtures
- Loose Tile Repair
- Cracks and Joints

Adheres To:

- *Ceramic/Porcelain*
- *Glass*
- *Most Plastics*
- *Granite, Cultured Marble & Natural Stone*
- *Wood*
- *Metal*
- *Drywall*
- *Fiberglass*
- *Painted Surfaces*

Performance Characteristics:

- Repels water, stains and dirt
- Lifetime mold & mildew resistance guarantee
- Stain proof protection
- Water ready in 4 hours
- 100% waterproof & crack proof
- Safe for granite & marble
- Easy water cleanup and low odor
- Not paintable
- **Sealant applies white and dries clear in 7-14 days (depending on joint depth, temperature and humidity).**

For Best Results:

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide by 3/8" deep. For joints deeper than 3/8", use backer rod.
- Store product away from extreme heat or cold.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old sealant, dirt, dust, debris and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size. If using the cartridge, puncture inner foil seal and load into caulk gun.
3. Fill gap with sealant, pushing sealant ahead of nozzle.
4. For a neat finish, smooth bead of sealant immediately with a finishing tool.
5. Allow sealant to dry for at least 4 hours before exposing to water. Sealant reaches full performance in 24 hours.
6. Clean up excess uncured sealant with damp sponge before it skins over. Scrape or cut away excess cured sealant.
7. Regular cleaning of surrounding areas is suggested.
8. Reseal tube/cartridge for future use.

Physical & Chemical Characteristics:

Tooling Time:	3-5 minutes
Tack Free Time:	8-10 minutes
Paintable:	No
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Acrylic Polymer
Volatile:	Water
Flash Point:	None
Filler:	Titanium Oxide
Density:	1.03
Solids:	58% by weight

Weight per Gallon:	8.60 lbs/gallon
Temperature Service Range:	0° F to 170°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles
Applications:	Interior
Shelf Life:	12 Months
Coverage:	5.5 fluid ounces: 30 linear feet at a 3/16" diameter bead or two average size bathtubs. 10.1 fluid ounces: 56 linear feet or four average size bathtubs.

Clean Up & Storage:

Remove excess uncured sealant with a damp cloth/sponge before it dries. After sealant has dried, excess sealant must be cut or scraped away. Store in a cool, dry place away from extreme heat or cold.

Safety:

For additional safety information, see product label or Safety Data Sheet. You can obtain an SDS sheet by going to www.dap.com and clicking on the SDS link next to the product or by calling 1-888-DAP-TIPS.

Lifetime Mold & Mildew Resistance Guarantee:

DAP guarantees that the product when properly applied will remain free of mold and mildew during the lifetime of your home. If mold and/or mildew appear when used as directed, provide evidence of mold and mildew and sales receipt to DAP Products Inc., 2400 Boston Street, Suite 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.