

PROPRIETARY BATTERY TECHNOLOGY

WORLD'S FIRST

Battery pack that automatically changes voltage when you change tools.



PARALLEL MODE = RUNTIME

In 20V MAX* tools the battery delivers up to 4 times the runtime.



SERIES MODE = POWER

In 60V MAX* tools the battery delivers the power of a corded tool.



FLEXVOLT™ 20V MAX* HAMMERDRILL / IMPACT DRIVER COMBO KIT

Features: •Up to 159 holes using 2-9/16" self feed bit in 2x10 SPF (Spruce/Pine/Fir) Lumber per charge •Patented 3-speed transmission •60 Lumens LED with 20-Min. Spotlight Mode

•Carburized Metal Ratcheting Chuck •820 UWO of Extreme Power

Kit Includes: 1/2" 3-Speed brushless hammerdrill, 1/4" 3-speed brushless impact driver, 60V MAX* FLEXVOLT™ 6.0Ah battery, 20V MAX* 2.0Ah Li-Ion battery, charger, (2) belt hooks, contractor bag, and 360° side handle.

Part No. DCK299D1T1.



Hammerdrill	Impact Driver
Max Power	820 UWO
Max RPM	0 to 450 / 0 to 1,300 / 0 to 2,000
Clutch Settings	11
Tool Weight	3.4 lbs.
	Anvil Type
	1/4" Hex
	No Load Speed
	0 to 1,000 / 0 to 2,800 / 0 to 3,250 RPM
	Impacts/Min
	0 to 3600 ipm
	Max Torque
	0 to 240 / 1500 / 1825 in-lbs.
	Tool Weight
	2.1 lbs.

FLEXVOLT™ 60V MAX* RECIPROCATING SAW KIT

Features: •Up to 158 cuts per charge •Keyless lever-action blade clamp for quick and easy blade changes •0 to 3,000 SPM and a 1-1/8" stroke length for fast and efficient cutting •Variable speed trigger allows user to instantly control speed •LED light helps to illuminate dark jobsite work areas •Pivoting shoe provides leverage for different applications •Rubber overmold grip for comfort

Kit Includes: 60V MAX* FLEXVOLT™ 6.0Ah battery, blade, fast charger, and kit bag.



Part No.	Description
DCS388T2	Kit includes (2) batteries
DCS388T1	Kit includes (1) battery
DCS388B	Tool only

Specifications	
Keyless Blade Clamp	Yes
Stroke/Min	0 to 3,000 SPM
Stroke Length	1-1/8"
Electric Brake	Yes
Tool Weight	7.8 lbs.

FLEXVOLT™ 60V MAX* 4-1/2" - 6" GRINDER KIT

Features: •Up to 126 cuts per charge •Brake engages when trigger is released, stopping speeds of 1.5 seconds with standard grinding wheel •Kickback Brake engages when a pinch, stall, or bind-up event is sensed and the electronic brake engages with maximum force to quickly stop the wheel, reduce the movement of the grinder, and shut the grinder off •E-Clutch activates in less than a tenth of a second when a pinch/stall is detected, shutting down the motor •9,000 RPM Speed allows the use of up to 6" wheels •Allows for up to 6" wheel size for both cutting and grinding applications

Kit Includes: 60V MAX* FLEXVOLT™ 6.0Ah batteries, fast charger, side handle, type 27 wheel, (2) type 27 guards, wrench, flanges, and kit bag.



Part No.	Description
DCG414T2	Kit includes (2) batteries
DCG414T1	Kit includes (1) battery
DCG414B	Tool only

Specifications	
MWO	1700W
Max Horsepower	2.2 hp
No Load Speed	9,000 RPM
Spindle Lock	Yes
Spindle Thread	5/8"-11
Tool Weight	4.66 lbs.

FLEXVOLT™ 60V MAX* 8-1/4" TABLE SAW KIT

Features: •Up to 302 linear feet per charge •Rack and pinion telescoping fence rails make fence adjustments fast, smooth and accurate •24" of rip capacity for ripping 4x8 plywood or OSB sheets •Runs off 20V/60V MAX* FLEXVOLT™ battery system for maximum portability •Site-Pro Modular Guarding System allows for tool free adjustments of the guarding •Power-Loss Reset prevents accidental re-starts following a power disruption when the tool is left in the "on" position •Metal roll cage base offers greater durability than plastic bases •On Board Storage for Guard, Fence, wrenches and miter gauge •Table coating reduces friction for smoother cutting

Kit Includes: 60V MAX* FLEXVOLT™ 6.0Ah battery, fast charger, blade, (2) blade wrenches, and push stick.



Part No.	Description
DCS7485T1	Kit
DCS7485B	Tool Only

Specifications	
No Load Speed	5,800 RPM
Blade Diameter	8-1/4"
Arbor Size	5/8"
Depth of cut at 45°	1-3/4"
Depth of cut at 90°	2-1/2"
Max rip to right of blade	24"
Max rip to left of blade	12-1/2"
Tool Weight	46.9 lbs.

FLEXVOLT™ 60V MAX* 1/2" VSR STUD & JOIST DRILL KIT

Features: •Up to 138 holes per charge •60V MAX* Brushless Motor for increase power and runtime •Adjustable bail handle and 2-position side handle for leverage and control •2 variable speed ranges (0-300 / 0-1250 RPM) to match appropriate speed to the application •E-Clutch is a Perform and Protect™ feature that detects reactionary torque caused by a bind-up or stall and reduces speed to a manageable level until control is regained. •Metal-gear housing for jobsite durability and increased reliability

Kit Includes: 60V MAX* FLEXVOLT™ 6.0Ah battery, fast charger, chuck key and holder, 2-position side handle, adjustable bail handle and kit bag.



Part No.	Description
DCD460T2	Kit includes (2) batteries
DCD460T1	Kit includes (1) battery
DCD460B	Tool only

Specifications	
Chuck Size	1/2"
No Load Speed	0 to 300 / 0 to 1250 RPM
Gear Reduction	Triple
Tool Weight	10.6 lbs.

FLEXVOLT™ 60V MAX* 7-1/4" CIRCULAR SAW KIT

Features: •Delivers up to 339 cuts per charge in 2" x 4 ft. SPF lumber •Depth of cut - 2-9/16" •Electronic brake - Stops the blade after the trigger is released •Brushless motor - Maximized for run time and durability 5,800 RPM optimized speed for quality cuts with speed

Kit Includes: 60V MAX* FLEXVOLT™ 6.0Ah battery, fast charger, blade, blade change wrench, and kit bag.



Part No.	Description
DCS575T2	Kit includes (2) batteries
DCS575T1	Kit includes (1) battery
DCS575B	Tool only

Specifications	
MWO	1,500
No Load Speed	5,800 RPM
Blade Diameter	7-1/4"
Bevel Capacity	0-57°
Arbor Size	5/8"
Depth of cut at 45°	1-7/8"
Depth of cut at 90°	2-9/16"
Shoe	Aluminum
Tool Weight	8.2 lbs.