



# Wire Management

When wires become entangled they are safety hazards, for both the equipment and the owner. Gardner Bender™ offers a variety of products for protection and neatness. As the needs of professional electricians change in managing wire and cable, Gardner Bender™ continues to deliver innovative solutions.

page 163




page 167



page 165



page 168



|   |          |
|---|----------|
| Anchor Kit - Plastic Conical .....                    | 171      |
| Box Supports/Spacers .....                            | 170, 172 |
| Cable Clamps - Plastic .....                          | 167      |
| Cable Clamps - Rubber Insulated .....                 | 167      |
| Cable Wraptor™ .....                                  | 163      |
| Duct Seal Compound .....                              | 169      |
| Grommets .....  | 168      |
| Hanger Strap .....                                    | 169      |
| Heat-Shrink Gun .....                                 | 164      |
| Heat-Shrink Tubing                                    |          |
| Thin Wall Polyolefin .....                            | 165      |
| Colored PVC .....                                     | 165      |
| Heavy-Wall .....                                      | 166      |
| Knockout Seals .....                                  | 168      |
| Reference Book - "Wiring Simplified" .....            | 172      |
| Reference Book - "Ugly's Electrical References" ..... | 172      |
| Screw Kits .....                                      | 171      |
| Seals .....   | 169      |
| Spiral Wrap .....                                     | 166      |
| Split Flex Tubing .....                               | 166      |
| Stud Insulators .....                                 | 168      |
| Tape  |          |
| Electrical .....                                      | 163      |
| Friction .....  | 164      |
| Silicone Self-Sealing .....                           | 164      |
| Liquid Electrical .....                               | 164      |
| Wire Markers - Pocket Pack .....                      | 170      |

**NEW Cable Wraptor™**

Simple design, endless solutions.

- “T” handle feature allows for easy carrying from one job to the next.
- Large hang hole is perfect to store and hang.
- Stainless steel hinge and spring to prevent rusting.
- Large teeth design for secure locking system.
- Easy release trigger.
- Cable tie looping hole for permanent attachment.
- Spring-loaded hinge helps close tail.

| Part #    | Pkg Qty | Bundle Dia. Max. | Size    |
|-----------|---------|------------------|---------|
| CW-T1RR50 | 50/box  | 1 1/8"           | small   |
| CW-T2RR25 | 25/box  | 2"               | medium  |
| CW-T3RR25 | 25/box  | 3"               | large   |
| CW-T4RR20 | 20/box  | 4"               | x-large |



Patented



**Electrical Tape**

Quality electrical tape designed for general purpose electrical applications.

- Made from low-lead PVC material.
- For applications up to 600 V.
- Temp rating up to 80 °C (176 °F).

| Part #    | Pkg Qty | Sleeve Qty | Width | Length | Color                                      |
|-----------|---------|------------|-------|--------|--|
| GTP-307   | 1/roll  | 10/sleeve  | 3/4"  | 30'    | Black                                      |
| GTP-307D  | 1/card  | —          | 3/4"  | 30'    | Black (w/Dispenser)                        |
| GTP-307WD | 1/card  | —          | 3/4"  | 30'    | Black - Weather Resistant (w/Dispenser)    |
| GTP-607   | 1/roll  | 10/sleeve  | 3/4"  | 60'    | Black                                      |
| GTP-607P  | 1/puck  | —          | 3/4"  | 60'    | Black                                      |
| GTB-667P  | 1/puck  | —          | 3/4"  | 60'    | Blue                                       |
| GTN-667P  | 1/puck  | —          | 3/4"  | 66'    | Brown                                      |
| GTO-667P  | 1/puck  | —          | 3/4"  | 66'    | Orange                                     |
| GTG-667P  | 1/puck  | —          | 3/4"  | 66'    | Green                                      |
| GTR-667P  | 1/puck  | —          | 3/4"  | 66'    | Red  |
| GTW-667P  | 1/puck  | —          | 3/4"  | 66'    | White                                      |
| GTY-667P  | 1/puck  | —          | 3/4"  | 66'    | Yellow                                     |
| GTPC-512  | 5/card  | —          | 3/4"  | 12'    | Assorted (Red, White, Blue, Green, Yellow) |
| GTPC-550  | 5/clam  | —          | 1/2"  | 20'    | Assorted (Red, White, Blue, Green, Yellow) |



## Friction Tape

Black friction tape with matted finish, available in two lengths.

- Matted finish provides the best gripping surface available.
- Use over electrical splices, wrapping grips or sporting goods.
- Available in two lengths: 30' or 60'.

| Part #  | Pkg Qty | Description       |
|---------|---------|-------------------|
| GTF-300 | 1/roll  | ¾" wide, 30' long |
| GTF-600 | 1/roll  | ¾" wide, 60' long |



## **NEW** Self Sealing Tape

High quality tape to insulate many conductor shapes.


- Insulates and seals surfaces
- Fuses to itself during application to stay watertight
- Silicone Tape provides permanent mold in 24 hrs, or in minutes with application of heat



RTP-3422



| Part #   | Pkg Qty | Description                       | Material | Max Voltage | Max Temp    | Min Temp    |
|----------|---------|-----------------------------------|----------|-------------|-------------|-------------|
| HTP-1010 | 1/roll  | 1" wide, 10' long                 | Silicone | 400V        | 500°F/260°C | -85°F/-65°C |
| RTP-3422 | 1/roll  | ¾" wide, 22' long, .031 mil thick | Rubber   | 600V        | 176°F/80°C  | —           |



HTP-1010

## **NEW** Liquid Electrical Tape

A liquid coating used to insulate and protect electrical splices and connections.

- Waterproof, will not unravel or deteriorate like traditional tape.
- Great for home, auto/marine and electrical applications.
- Indoor/outdoor.
- Brush-on applicator included.

| Part #  | Pkg Qty     | Color | Part #  | Pkg Qty     | Color |
|---------|-------------|-------|---------|-------------|-------|
| LTB-400 | 4 oz/bottle | Black | LTW-400 | 4 oz/bottle | White |
| LTR-400 | 4 oz/bottle | Red   | LTS-600 | 6 oz/spray  | Black |
| LTG-400 | 4 oz/bottle | Green |         |             |       |



## **NEW** Heat Shrink Gun

- Use with heat shrink tubing or terminals.
- Refillable butane can included.

| Part #     | Pkg Qty |
|------------|---------|
| MSTR-TORCH | 1/clam  |



## Thin-Wall Heat-Shrink Tubing – Polyolefin

Great for cable insulation, marking and bundling, with superior mechanical, abrasion and moisture protection.

- Flame retardant.
- Resists common fluids and solvents.
- Meets UL 224, 125 °C; CSA C22.2 No. 198.1, 125 °C; MIL-DTL-23053/5, Class 1 & 2, AMS 3636 & 3637; DEF STAN 59-79, Issue 3 Type 2a.
- Continuous operating temperature: -55 °C (-67 °F) - 135 °C (275 °F).
- Shrink temperature: 120 °C (250 °F) - 250 °C (480 °F).
- 600 V/Mil Dielectric strength.
- 2:1 shrink ratio.



|            | Part #  | Pkg Qty           | Inside Diameter    |          | Length | Conductor Gauge AWG* |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |     |   |
|------------|---------|-------------------|--------------------|----------|--------|----------------------|----|----|----|----|----|----|----|---|---|---|---|---|-----|-----|-----|-----|---|
|            |         |                   | Before             | Finished |        | 24                   | 22 | 20 | 18 | 16 | 14 | 12 | 10 | 8 | 6 | 4 | 2 | 1 | 1/0 | 2/0 | 3/0 | 4/0 |   |
|            |         |                   |                    |          |        |                      |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |     |   |
| Polyolefin | HST-093 | 8 pcs             | 3/32"              | 3/64"    | 4"     | ●                    |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |     |   |
|            | HST-125 | 7 pcs             | 1/8"               | 1/16"    | 4"     | ●                    | ●  | ●  |    |    |    |    |    |   |   |   |   |   |     |     |     |     |   |
|            | HST-187 | 8 pcs             | 3/16"              | 3/32"    | 4"     |                      | ●  | ●  | ●  | ●  | ●  |    |    |   |   |   |   |   |     |     |     |     |   |
|            | HST-250 | 6 pcs             | 1/4"               | 1/8"     | 4"     |                      |    | ●  | ●  | ●  | ●  | ●  |    |   |   |   |   |   |     |     |     |     |   |
|            | HST-375 | 3 pcs             | 3/8"               | 3/16"    | 4"     |                      |    |    |    |    | ●  | ●  | ●  | ● | ● | ● |   |   |     |     |     |     |   |
|            | HST-500 | 3 pcs             | 1/2"               | 1/4"     | 4"     |                      |    |    |    |    |    | ●  | ●  | ● | ● | ● | ● |   |     |     |     |     |   |
|            | HST-750 | 2 pcs             | 3/4"               | 3/8"     | 4"     |                      |    |    |    |    |    |    |    |   | ● | ● | ● | ● | ●   | ●   | ●   | ●   | ● |
|            | HST-999 | 2 pcs             | 1"                 | 1/2"     | 4"     |                      |    |    |    |    |    |    |    |   |   |   |   |   |     |     | ●   | ●   | ● |
| HST-AST    | 8/card  | 1/8", 3/16", 1/4" | 1/16", 3/32", 1/8" | 4"       |        |                      |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |     |   |




\* Sizes shown are approximate and may vary according to manufacturer and insulation system for each wire.

## **NEW** Colored Heat-Shrink Tubing – PVC

Great for general-purpose applications.

- Flame retardant.
- Meets UL 224 VW-1; CSA C22.2 No. 198.1 OFT.
- Continuous operating temperature: -30 °C (-22 °F) - 105 °C (220 °F).
- Shrink temperature: 110 °C (230 °F).



HST-101



HST-107



|     | Part #  | Pkg Qty                | Inside Diameter        |          | Length         | Conductor Gauge AWG* |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     | Color |  |                                 |
|-----|---------|------------------------|------------------------|----------|----------------|----------------------|----|----|----|----|----|----|----|---|---|---|---|---|-----|-----|-----|-------|--|---------------------------------|
|     |         |                        | Before                 | Finished |                | 24                   | 22 | 20 | 18 | 16 | 14 | 12 | 10 | 8 | 6 | 4 | 2 | 1 | 1/0 | 2/0 | 3/0 |       |  |                                 |
|     |         |                        |                        |          |                |                      |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |       |  |                                 |
| PVC | HST-100 | 8'/clam                | 3/16"                  | 3/32"    | 8'             | ●                    | ●  | ●  | ●  | ●  |    |    |    |   |   |   |   |   |     |     |     |       |  | Red                             |
|     | HST-101 | 8'/clam                | 1/4"                   | 1/8"     | 8'             |                      |    | ●  | ●  | ●  | ●  |    |    |   |   |   |   |   |     |     |     |       |  | Blue                            |
|     | HST-102 | 8'/clam                | 5/16"                  | 5/32"    | 8'             |                      |    |    |    |    | ●  | ●  | ●  | ● | ● |   |   |   |     |     |     |       |  | Yellow                          |
|     | HST-107 | (7)-3" pieces/<br>clam | 1/8", 1/4", 3/8", 1/2" |          | (7)-<br>3" pcs |                      |    |    |    |    |    |    |    |   |   |   |   |   |     |     |     |       |  | Assorted<br>(Red, Blue, Yellow) |

\* Sizes shown are approximate and may vary according to manufacturer and insulation system for each wire.

## Heavy-Wall Heat-Shrink Tubing

Provides maximum reliability for insulating and protecting wire, cables and terminations.

- High impact, abrasion and corrosion resistance.
- Submersible and great for direct burial installations.
- Inner adhesive bonds to plastics, rubber, neoprene, steel, polyethylene.
- Continuous operating temperature: -55 °C (-67 °F) - 125 °C (257 °F).
- Shrink temperature: 120 °C (250 °F).



| Part #   | Pkg Qty | Inside Diameter |          | Length |
|----------|---------|-----------------|----------|--------|
|          |         | Before          | Finished |        |
| HWT-0722 | 1/bag   | 3/4"            | 7/32"    | 6"     |
| HWT-1138 | 1/bag   | 1 3/32"         | 3/8"     | 6"     |
| HWT-1550 | 1/bag   | 1 1/2"          | 1/2"     | 6"     |



## Split Flex Tubing

Protects hoses, wire and cables from cuts, abrasions and UV wear.

- Excellent for managing cords for electronics, under hood or trailer wiring.
- Corrugated for added flexibility.
- Split down the center for wire breakout where needed.




| Part #    | Inside Dia. | Length | Color | Pkg Qty |
|-----------|-------------|--------|-------|---------|
| FLX-3810  | 3/8"        | 10'    | Black | 1/bag   |
| FLX-5007  | 1/2"        | 7'     | Black | 1/bag   |
| FLX-757GR | 3/4"        | 5'     | Gray  | 1/bag   |
| FLX-1007  | 1"          | 5'     | Gray  | 1/bag   |

## Spiral Wrap

Manages wire and cable neatly and allows for cable to break out at desired locations.

- Made from flexible polyethylene.
- Protects cables from cuts, abrasions and UV wear.



| Part #  | Description | Color | Includes: |             |             |
|---------|-------------|-------|-----------|-------------|-------------|
|         |             |       | Qty       | Description | Inside Dia. |
| FSP-AST | Assorted    | Clear | 1         | 4' length   | 3/8"        |
|         |             |       | 1         | 4' length   | 1/8"        |


## Plastic Cable Clamps

Polypropylene clamps hold harnesses, cables and tubing.

- Used for construction, maintenance and assembly-line operations.
- Use in control cabinets, panels and general applications.
- Tough, durable, yet extremely lightweight.
- Working temperature range: -54 °C (-66 °F) to 170 °C (340 °F).
- Clean, smooth edges for easy handling.
- Fast installation.



| Part #      | Pkg Qty | Dimensions |        |       |       |         | Color   |
|-------------|---------|------------|--------|-------|-------|---------|---------|
|             |         | A dia.     | B      | C     | D     | E width |         |
| PPC-1525    | 18/card | 1/4"       | 25/64" | 1/32" | 3/64" | 3/8"    | Natural |
| PPC-1525UVB | 18/card | 1/4"       | 25/64" | 1/32" | 3/64" | 3/8"    | Black   |
| PPC-1538    | 15/card | 3/8"       | 31/64" | 1/32" | 3/64" | 3/8"    | Natural |
| PPC-1538UVB | 15/card | 3/8"       | 31/64" | 1/32" | 3/64" | 3/8"    | Black   |
| PPC-1550    | 12/card | 1/2"       | 35/64" | 3/64" | 3/64" | 3/8"    | Natural |
| PPC-1550UVB | 12/card | 1/2"       | 35/64" | 3/64" | 3/64" | 3/8"    | Black   |
| PPC-1575    | 6/card  | 3/4"       | 3/64"  | 3/32" | 3/64" | 1/2"    | Natural |
| PPC-1575UVB | 6/card  | 3/4"       | 3/64"  | 3/32" | 3/64" | 1/2"    | Black   |
| PPC-1600    | 4/card  | 1"         | 51/64" | 3/32" | 3/64" | 1/2"    | Natural |



## Rubber Insulated Clamps

Secures wire and cable in industrial, auto/marine and where vibrations may occur.

- Corrosive-resistant plated steel clamp.
- Flexible 1/2" wide body.
- Secure with 1/4" screw.

| Part #   | Size | Pkg Qty |
|----------|------|---------|
| PPR-1550 | 1/2" | 2 pcs   |
| PPR-1575 | 3/4" | 2 pcs   |
| PPR-1600 | 1"   | 1 pc    |



## Plastic Kwik Clips

Mount bundles, cables, cords, tools etc. to drywall, wood and painted surfaces.

- Ratcheting/releasable feature allows adjustment to a range of bundle diameters.
- Adhesive backed.

| Part #      | Pkg Qty | Description      | Color   |
|-------------|---------|------------------|---------|
| GKK-1538    | 6/card  | Holds 3/8" Cable | Natural |
| GKK-1538UVB | 6/card  | Holds 3/8" Cable | Black   |
| GKK-1550    | 4/card  | Holds 1/2" Cable | Natural |
| GKK-1575    | 2/card  | Holds 3/4" Cable | Natural |





## Stud Insulators

One piece design insulating 360° protection for cable runs through metal studs.

- Fits all pre-punched and field punched hole sizes and configurations.
- Unique folding tabs for fast, one-handed installations.
- Meets NEC article 300-4(b) and CEC rule 12-516.

| Part # | Pkg Qty | Description           |
|--------|---------|-----------------------|
| SI-25N | 25/bag  | Metal Stud Insulators |



Patented

SEE PG  
**113**



FOR MORE INFO ON  
**Stud Punch**

## Grommets

Protect wires from chafing against drilled holes.


| Part #   | Pkg Qty | Inside Dimensions      |
|----------|---------|------------------------|
| GHG-1525 | 6/card  | 1/4"                   |
| GHG-1538 | 5/card  | 3/8"                   |
| GHG-1550 | 4/card  | 1/2"                   |
| GHG-1575 | 3/card  | 3/4"                   |
| GHG-AST  | 8/clam  | 1/4", 3/8", 1/2", 3/4" |



## Knockout Seals (1/2" to 4")


Easy-to-use metal knockout seal.

- Fast and easy to install from inside or outside of box.
- Embossed for quick self-centering in unused knockouts. One screw holds seal in place.
- Made of rust-proofed, cold-rolled galvanized steel. Screw and bar are zinc-plated.
- Marked for size and catalog number for easy identification.
- 16-gauge steel; 3/8" thread.



| Part # | Pkg Qty | For Knockout Dia |
|--------|---------|------------------|
| KO701  | 100/box | 1/2"             |
| KO701C | 5/clam  | 1/2"             |
| KO702  | 50/box  | 3/4"             |
| KO702C | 3/clam  | 3/4"             |
| KO703  | 25/box  | 1"               |
| KO704  | 25/box  | 1 1/4"           |

| Part # | Pkg Qty | For Knockout Dia |
|--------|---------|------------------|
| KO705  | 10/box  | 1 1/2"           |
| KO706  | 10/box  | 2"               |
| KO707  | 10/box  | 2 1/2"           |
| KO708  | 10/box  | 3"               |
| KO709  | 10/box  | 3 1/2"           |
| KO710  | 10/box  | 4"               |



SEE PG  
**104**



FOR MORE INFO ON  
**Hydraulic Drivers & Pull Studs**



## Snap-In Seals (1/2" to 2")

Convenient snap-in feature for quick installation.

- Zinc-plated to resist corrosion.

| Part # | Pkg Qty | For Knockout Dia. |
|--------|---------|-------------------|
| 601    | 100/box | 1/2"              |
| 602    | 100/box | 3/4"              |
| 603    | 50/box  | 1"                |



SEE PG **107** FOR MORE INFO ON **Knockouts**

## Galvanized Hanger Strap

For hanging or fastening conduit, pipe or cables.

- Flexible for easy use.





| Part #   | Pkg Qty | Description           |
|----------|---------|-----------------------|
| GHS-1510 | 1/card  | 10' x 3/4" x 20 gauge |

## Saf-Te-Plate™ Protectors

Protects cable and plastic pipe from nail punctures.

- Plate attaches to wood studs with a single hammer blow.
- Required for compliance with NEC 1990 Article 300-4A.



| Part #  | Pkg Qty | Description                               |
|---------|---------|---|
| FP159-3 | 100/box | 1 1/2" x 3" x 16 gauge Metal Safety Plate |
| FP159-6 | 50/box  | 1 1/2" x 6" x 16 gauge Metal Safety Plate |

## Duct Seal Compound

Seals conduit openings against drafts, dust, moisture and noise.

- Protects terminal boxes, pot heads and bushings from corrosive elements.
- Deadens switch gear panel noise.
- Dough-like compound is easily "thumbed" over holes and gaps.
- Will not harden or form a skin under normal conditions.
- Not for use outdoors.
- Specifications:
  - Viscosity: ASTM D-217 300-gram load - 7.0 -11.0; ASTM DS-S2 100-gram load - 9.0 -15.0
  - Temperature Range: Adheres at -20 °F (-29 °C). Will not slump after 1 hr. at 350 °F (175 °C).
  - Flash Point: Over 550 °F (285 °C).
  - Other Properties: Non-conducting, non-deteriorating, non-toxic, non-corrosive, non-staining, non-curable; 99% solid, coil-based.



| Part # | Pkg Qty | Description |
|--------|---------|-------------|
| DS-130 | 30 pugs | 1 lb Pugs   |
| DS-530 | 6 pugs  | 5 lb Pugs   |

## Pocket Pack Wire Markers

Pocket-sized booklets of cloth wire markers and matching terminal markers.

- Saves time and money during all on-site and in-plant initial hookup, troubleshooting, maintenance and repair.
- Nylon-impregnated cloth resists moisture, dirt and oil.
- Non-smear legends assure high visibility for instant, positive identification.
- Matching terminal marker with every wire marker, plus an extra page of blank write-on wire and terminal markers for special legends.





| Part #   | Marker Legends                  | Qty   |
|----------|---------------------------------|-------|
| 42-027   | 0 - 9                           | 45/ea |
| 42-028   | A - Z                           | 10/ea |
|          | 0 - 15                          | 10/ea |
|          | Symbols: +, -, /                | 10/ea |
| 42-029   | 1 - 45                          | 10/ea |
| 42-030   | 46 - 90                         | 10/ea |
| 42-035   | 1 - 15                          | 6/ea  |
|          | 16 - 90                         | 4/ea  |
|          | A - Z                           | 2/ea  |
|          | Symbols: +, -, /, 0             | 2/ea  |
| 42-ALPHA | Circuit Breaker Box Marker Book |       |

## Box Supports

Saves time for installing outlet or switch boxes.

- Screwless support for ease of use.
- Simple to use:
  1. Mark corners of box position and drill four 1/2" holes.
  2. Saw between holes to make box opening.
  3. Place box into opening.
  4. Slip box supports into openings alongside box; one with long end up, the other down.
  5. Bend fingers of box supports into box while firmly pressing box against wall.



| Part # | Pkg Qty     | Description            |
|--------|-------------|------------------------|
| 800    | 25 sets/box | Box Support Set (pair) |



**NEW Electrician's Screw Kits**



Assorted sizes & lengths of commonly used electrical machine screws.

- Slotted round-head screws for switches, receptacles and outlet applications.
- Slotted flat-head screws for all-purpose electrical fastening.

| Part #   | Pkg Qty | Type              | Contents  |
|----------|---------|-------------------|---|
| SK-832   | 370 pcs | 8-32 Round Head   | 1/2", 3/4", 1", 1 1/4", 1 1/2", 2"  |
| SK-632   | 370 pcs | 6-32 Flat Head    | 3/4", 1", 1 1/4", 1 1/2", 2", 3"  |
| SK-832WP | 135 pcs | 8-32 Round Head   | 1/2", 3/4", 1", 1 1/4", 1 1/2", 2"<br>wall plate screws (white, ivory & almond) |
| 14-WPI   | 10/card | Wall Plate Screws | Ivory   |
| 14-WPW   | 10/card | Wall Plate Screws | White   |



SK-832WP



**Big Red™ Plastic Conical Anchor Kit**


Perfect multi-purpose kit for professionals and end-users.

- Tapered end for easy installation.
- Flanged ribs prevent turning or twisting in hole.
- Carbide drill bit included with each kit.

| Part #   | Pkg Qty | Description        |
|----------|---------|--------------------|
| AP4-K100 | 1 kit   | Plastic Anchor Kit |

**Kit Contains:**


| Qty | Description  |
|-----|--|
| 100 | 1/4" x 1" Anchors                                    |
| 100 | #10 x 1" Slot/Phillips Combo Head Sheet-Metal Screws |
| 1   | 1/4" Carbide Drill Bit                               |



## Quick Fix Spacers

Adjusts length of receptacle or switches for proper fit of face plates.

- Four-inch stack of spacers twists apart easily for desired thickness.



| Part # | Pkg Qty  | Description |
|--------|----------|-------------|
| GSP-04 | 4 strips | Spacers     |

## **NEW** Electrical Reference Books

Reference books that outline safe wiring recommendations based on the National Electric Code.

| Part # | Pkg Qty | Description  |
|--------|---------|--|
| ERB-UG | 1       | <i>Ugly's Electrical References - Revised 2011 Edition.</i><br>A quick, on-the-job reference guide for the most commonly required information in an easy-to-read format.           |
| ERB-WS | 1       | <i>Wiring Simplified 43rd Edition</i><br>A comprehensive book that translates the NEC rules into easy-to-understand explanations on how to complete safe wiring installs in homes. |

