GRAVEL

PRO-TURN® 100

Succeed, Don't Settle.

Every inch brings value to the Pro-Turn 100. Packed with Gravely's time-tested features, this hard-working mower stands up to your toughest jobs.

GRAVEI

X-FACTOR' II DECK The 7-gauge, all-steel welded X-Factor' II Deck is fabricated from top to bottom, providing industrial-strength peace of mind that's reinforced with an exclusive limited lifetime warranty.

PBBA

CBT SYSTEM our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent. **ROPS** foldable ROPS comes standard to provide additional protection for the operator.

INSIGHTFUL DESIGN an updated design improves the operator experience, providing a clear line of sight to the deck cutting edge.

SEATING SYSTEM the high-back suspension seats provides improved lateral stability with added vibration control and a 4-inch seat slide for all-day comfort.



NO HOUR LIMIT FIRST TWO YEARS LIMITED LIFETIME DECK SHELL & FRAME

See your professional Gravely® dealer for complete warranty details.



	148	152	152	152	160	160	160	160
MODEL NUMBER	991128	991129	991132	991135	991130	991133	991136	991140
ENGINE	KAWASAKI® FX691V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KAWASAKI® FX691V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT730 AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® EZT725 EFI AIR-COOLED, HEAVY-DUTY AIR CLEANER	KAWASAKI® FX730V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® EZT740 AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT740 EFI AIR-COOLED, HEAVY-DUTY AIR CLEANER	YAMAHA® MX800 AIR-COOLED, HEAVY-DUTY AI CLEANER
HORSEPOWER	22 HP	22 HP	23 HP	22 HP	23.5 HP	25 HP	25 HP	26 HP
DISPLACEMENT (CC)	726 CC	726 CC	747 CC	725 CC	726 CC	747 CC	747 CC	824 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3400 TRANSAXLES							
FUEL CAPACITY – Gallons (Liters)	10 GAL.							
GROUND SPEED (Approx. Mph) (Forward/Reverse)	10 MPH / 5 MPH							
DECK								
DECK MATERIAL	7 GA. STEEL W/ 1/4 IN. SPINDLE REINFORCEMENT							
DECK CONSTRUCTION	FABRICATED							
NUMBER OF SPINDLES	3							
BLADE TIP SPEED (FPM)	18,000							
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM							
SPINDLE BEARINGS	BALL BEARING							
DECK ENGAGEMENT	OGURA® GT2.5 ELECTRIC CLUTCH							
CUTTING WIDTH	48 IN.	52 IN.	52 IN.	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN 5.5 IN.							
CUTTING POSITIONS	17							
WHEELS								
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES							
FRONT	SM00TH 13 X 6.50-6							
REAR	TURF 23 X 10.50-12							
FEATURES								
SEAT	HIGH BACK W/ FULL SUSPENSION							
FOLDABLE ROPS	STANDARD							
MACHINE								
WEIGHT	1062 LBS.	1079 LBS.	1068 LBS.	1073 LBS.	1121 LBS.	1110 LBS.	1115 LBS.	1136 LBS.
LENGTH	78.5 IN.							
WIDTH (W/O CHUTE)	50 IN.	55.5 IN.			63 IN.			
WIDTH (W/ CHUTE)	62 IN.	67.5 IN.			75 IN.			
HEIGHT (W/ ROPS EXT/DOWN)				71 IN.	/ 48 IN.			
WARRANTY								
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS							
DECK SHELL & FRAME	LIMITED LIFETIME							
ATTACHMENTS & ACCESSORIES								
MULCHING KIT, DISCHARGE COVER								

AN ARIENS CO BRAND

© Copyright 2019 AriensCo. All rights reserved. Registered trademark and " trademark of Ariens Company. Briggs & Stratton", Kohler", Kawasaki", Subaru", Yamaha" and Hydro-Gear" are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

