


Majic Water Sealer

8-0165

DESCRIPTION

Majic Water Sealer provides a water-tight shield. It dries to a clear finish that prevents moisture from seeping into the surface. Majic Water Sealer provides long lasting water-repellent protection on concrete, wood, canvas and brick.



FEATURES

- Ideal for wood, canvas, masonry and concrete
- Blocks moisture from penetrating into the surface
- Prevents swelling and shrinking of wood

VOC / MIR (sprays)

250 gm/l
(2.10 lbs/gal)

NET WEIGHT

8.36 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/53 lbs
4-gal case/43 lbs

AVAILABLE COLORS

8-0165 Clear

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 48 hours for traffic	DRYTIME-RECOAT 4-24 hours	WET/ FILM THK 2 - 4 mils	FILM THK /DRY: .1 - .2 mils	FINISH Matte	GLOSS n/a
FLASHPOINT > 200° F	COVERAGE 75 to 150 sq ft/gal	VISCOSITY 15 - 19"# 2 Zahn	VEHICLE Acrylic Emulsion	SOLVENT Water	

SURFACE PREP

Surface must be thoroughly dry and clean, free of oil, grease, dirt, loose mortar, etc. Water Sealer may cause bleeding on internal color in white bricks and certain color coatings on stucco and masonry. Test a small area to insure compatibility before proceeding. Use a block filler on highly porous cinder block before applying this product.

IMPORTANT NOTES: Do not use this product below grade or other areas where water pressure may exist. Do not use on rubber, asphalt base materials or certain plastics and synthetics. Apply a test patch if unsure. Do not expose freshly treated articles to fire or flame. Protect plants with plastic or canvas drop cloths. Some water based adhesives will bond to waterproofed surfaces.

APPLICATION

Stir well before using. A test patch to insure compatibility is recommended before coating entire surface. Apply generously with brush, roller or low pressure spray to point of saturation without leaving any excess on horizontal areas. Temperature should be above 50°F. Water Sealer may be applied on previously painted surfaces if porous enough to allow penetration of sealer. Two coats are recommended on surfaces that are not to be painted. Allow the first coat to dry 4-24 hours before recoating.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.