



PENOFIN VERDE

Odorless Zero VOC Interior/ Exterior Formula

Less than .1 gram per liter. Verde can be safely and effectively used in both exterior and interior applications. It is virtually odorless, containing no toxins or heavy metal compounds and has no discernable off-gassing properties.

Twice the Coverage

Verde covers 175-300 sq. ft. per gallon depending on the texture and condition of the wood

Deeply Penetrating Formula

High Performance, deep penetrating formula using our Brazilian Rosewood Oil creates a highly durable finish that lasts, with the same effortless maintenance of our other Penofin products! Never strip or sand again. Simply clean the wood and apply a light coat to enhance or restore the wood's natural beauty.

Easy Soap and Water Clean Up

Because Verde contains only natural vegetable based ingredients it is easily cleaned with soap and water.

Safe to Use Around Children and Animals

Verde dries to the touch in four hours and leaves no harmful residue. Safe for play equipment and animal shelter.





Penofin The World's Finest Wood Finish ®

Product Data Sheet

VERDE Quality, Beauty, Durability

A semi-transparent, penetrating oil finish manufactured to the highest environmental standard. may be cleaned initially with Penofin Pro-Tech contains no petroleum bi-products and it is Tt completely safe for use around children and animals. Containing no hazardous substances, Verde uses new green technology and materials which are made from sustainable plant based ingredients. Verde is the (eco) selection. logical choice of architects, green building contractors, professionals and woodworking environmentallv conscious consumers.

Penofin Verde contains only sustainable ingredients. It is virtually odorless, and does not off gas. It exceeds all environmental air quality standards wood is hot to the touch. Using a brush, pad, or and meets LEED criteria for Green Building.

The highest guality Brazilian Rosewood and other natural oils are combined with select vegetable ester solvents and zero VOC pigments resulting in a finish that is as durable as it is beautiful.

PERFORMANCE FEATURES:

- Non-Hazardous .
- Interior/Exterior Use Dries to touch in 4
- Non-Film Forming • •
 - VOC < .1 g/l
- Virtually Odorless • 99% UV
 - Natural Oil Beauty Preserves and Protects
 - Extends Life of Wood

VERDE APPLICATIONS:

Wood Decks .

Protection

Cabinetry •

hrs

- Log Homes • •
- Spas Docks
- Exterior Siding
- Furniture • Fences
- Floors • Doors

•

- Wood Art Windows

TECHNICAL DATA:

VOC: <.1 g/l Odor: very mild to none **Bio-Based Content:** > 95% Installation Temperature: 45° F (7 C) to 80° F (26 C). Relative Humidity: 85% maximum, below, below 80% for best results.

Dry to Touch: 4 hours Serviceable: 12 hours Full Cure: 4-7 days



APPLICATION:

Apply to clean, dry, bare wood. The wood Cleaner Step 2. New wood can be dirty from transport and construction, and should be cleaned before application. Always test an inconspicuos area to ensure proper surface preparation and color

Stir this product thouroughly before and during application. Apply at temperatures above 45°. Verde is stable under freeze/ thaw conditions. For optimum performance bring the stain to room temperature before application. Do not apply if the pump sprayer apply a liberal coat to the wood. Protect, tarp or mask off any adjacent areas you do not wish to stain. Verde is a penetrating finish and will penetrate any pourus surface. Allow Verde 10-20 minutes to penetrate into the wood. This step is important as it allows the finish to coat the individual fibers of the wood, protecting your investment from the inside out.

After 10-20 minutes wipe the surface thouroughly with clean lint free cloths to remove any excess finish. Verde is a penetrating finish and is not a surface coating. Not wiping will allow the finish to dry on the surface of the wood and will result in a tacky finish. Soak any wiping cloths in a bucket of water to avoid the possibility of spontaneous combustion which can occur with any oil based product.

CLEAN-UP:

Soap & Water

DRY TIME:

Verde will dry to the touch in 4 hours and is servicable after 12 hours.

MAINTENANCE:

Exterior Application:

Keep the wood clean, free of debris or standing water for long periods of time. Twice yearly, clean the surface with Penofin Pro -Tech Cleaner Step 2. Follow with Penofin Pro-Tech Brightener Step 3, if wood has graved or started to darken. Allow the wood to dry and simply coat any areas that might show wear or tear from furniture or scratches with another light application of Verde.

Interior Application:

Sweep, dust or vacuum regularly and clean with a damp mop or rag.

Please visit our website www.penofin.com for more application & wood care tips, or call our live customer service line at:

1 800 PENOFIN Monday—Friday 7-4 Pacific Time, or email us at mail@penofin.com.

Performance Coatings Inc Ukiah, California