

Product data sheet

Characteristics

QO2100CP

QO Mini CB 100 A 2P 120/240 V 10 kA Plug-in Mount

Product availability : Stock - Normally stocked in distribution facility



Price* : 189.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	100 A
System Voltage	120 V AC 120/240 V AC 48 V DC
Mounting mode	Plug-in
Poles description	2P
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Box lugs
Type of packing	Consumer packaging

Complementary

Breaking capacity	10 kA at: 120/240 V AC 5 kA at: 48 V DC 10 kA at: 120 V AC
Number of spaces required	2
AWG gauge	AWG 4...AWG 2/0 (copper or aluminium)
Height	3.5 in
Depth	2.91 in
Width	1.5 in

Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01343 - QO 2 POLE 70-125 AMP
Discount Schedule	CPQ
GTIN	00047569522291
Nbr. of units in pkg.	1
Package weight(Lbs)	0.70999999999999996
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

QO2100CP is replaced by:



QO(B) Circuit Breakers QO2100

QO Mini CB, 100A, 2P, 120/240V, 10kA, Plug-in Mount

Qty 1

Reason for Substitution: End of life | Substitution date: 01 January 2017