



# Valspar® Professional Interior Latex Eggshell Paint

## No. 11800 Series

### GENERAL DESCRIPTION

A premium quality, high hiding flat finish designed for interior walls and ceilings. Formulated for the professional, it sprays and rolls with low spatter.

### PRODUCT FEATURES

- High hiding
- Superior touch up
- Washable
- Low odor, low VOC
- Low spatter
- Easy application
- Soap and water clean up

### RECOMMENDED USES

- Drywall
- Plaster
- Masonry
- Primed wood or metal
- Previously painted surfaces

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

**Base and Fill Levels**  
(oz./gal.)

High Hiding White	128
Light Base (11811)	124
Medium Base (11812)	120
Neutral Base (11814)	116

### APPLICATION AND CLEANUP

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply only when paint, surface and air temperatures are 50–90 °F (10–32 °C) during application and drying time. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Clean up with warm, soapy water.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.017–0.021"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### SYSTEM

#### RECOMMENDATIONS

**Drywall/Wallboard (new):**

- 1 Coat: Valspar® New Construction Primer (11287)
- 1–2 Coats: Professional Interior Latex Eggshell

**Plaster:**

- 1 Coat: Valspar® Interior PVA Primer (11288)
- 1–2 Coats: Professional Interior Latex Eggshell

**New Wood/Composition Board:**

- 1 Coat: Valspar® Int/Ext Bonding Primer (11289)
- 1–2 Coats: Professional Interior Latex Eggshell

**Interior Concrete Block:**

- 1 Coat: Block filler
- 1–2 Coats: Professional Interior Latex Eggshell

**Concrete/Masonry:**

- 1 Coat: Valspar® Masonry and Stucco Primer (2935)
- 1–2 Coats: Professional Interior Latex Eggshell

**Previously Painted Surfaces:**

- 1–2 Coats: Professional Interior Latex Eggshell

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Vinyl copolymer

**Pigment Type:** Titanium dioxide

**Viscosity:** 90–100 Krebs Units

**Sheen:** 10–20 Units @ 85° angle

**Flashpoint:** N/A

**VOC (g/L):** less than 50 g/L

**VOC (lbs./gal.):** 0.36

**Volume Solids:** 31%

**Weight Solids:** 46%

**Weight Per Gallon:** 10.6 lbs./gal.

**Practical Coverage:** Covers up to 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L). Less on rough or porous surfaces. Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.

**Recommended Film Thickness:**

- 4.0 mil Wet
- 1.2 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 hour

**Recoat:** 4 hours

**Washing:** Allow at least 7 days before washing.

Use mild detergent and sponge.

**Application Temperature:** 50–90 °F (10–32 °C)

**Storage Temperature:** 40–90 °F (5–32 °C)

### CERTIFICATIONS

Current as of: 6/18/2014

MPI #	No
MPI GPS 1	No
MPI GPS 2	No
LEED (US)	NC 2.2
LEED (Canada)	NC 1.0

### REGULATORY COMPLIANCE

Current as of: 6/18/2014

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.



# Valspar® Professional Interior Latex Eggshell Paint

---

## No. 11800 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint and other foreign matter. Remove gloss from shiny surfaces. Repair all cracks and nail holes with patching compound. Painting over wallpaper is not recommended. New or bare surfaces should be primed with an appropriate Valspar® primer.

#### **Drywall and Plaster:**

Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® New Construction Primer (11287).

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Bonding Primer (11289).

#### **Concrete Block:**

Masonry surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with block filler, then top coat.

#### **Masonry/Concrete:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer (2935).

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions, and excludes failure due to deterioration of the underlying surface, structural defects, or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

#### **EMERGENCY MEDICAL TELEPHONE:**

**1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 6/18/14

Version: 11800B