



Oil Barn and Fence Paint



Product Description

Valspar Barn & Fence Oil Paint is easy to apply and affords long-lasting protection when applied according to label directions. It flows on smoothly and dries to a tough, durable finish. Fade and weather resistant and gives mildew resistant coating.

Features

- Fade and Weather Resistant
- Mildew resistant coating

Recommended Uses

- Interior and exterior barn surfaces
- Fences
- Sheds
- Silos
- Wood or aluminum siding
- Stucco or primed metal

Colors and Part Numbers

	Part Number
Red	2121-11 (Gallon) 2125-11 (5 Gallon)
White	3141-75 (Gallon) 3145-75 (5 Gallon)

Typical Properties (18-2121-11 Series)

Vehicle Type: Alkyd Resins

Sheen: 60+ Units @ 60° angle

Solids by Volume: 52%

Solids by Weight: 69%

Weight per Gallon: 10.2 lbs./gal.

VOC: Less than 380 g/L

Viscosity: 80–85 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 24 hour(s)

Recoat: 24 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 7 day(s)

Surface Coverage:

400 sq. ft./gal.

At: 4.0 mil Wet, 2.1 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.
- **DANGER:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallons – 4 per carton
5 Gallon Pails

PDS 18-2121

Surface Preparation

Read the Lead Warning in Cautions section. Clean surface thoroughly. Remove dirt, grease and oil with a non-residue all-purpose cleaner. Wash dirt from protected areas, such as under eaves. Remove loose or peeling paint and rust with a wire brush. Dull glossy areas with gloss remover, sandpaper or steel wool. Caulk cracks and crevices around windows, doors and trim. Prime unpainted wood or badly weathered surfaces with a first coat of Oil House Primer before painting. For metal roofs, tin or iron surfaces, gutters and downspouts, make sure surface is clean. Remove all loose paint, rust and scale before painting. Prime with a rust-inhibitive metal primer. Do not paint in hot sunlight. **Clean mildew from the surface:** Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before finishing or it will grow through any new coating. To remove mildew, scrub with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts of water. Rinse thoroughly and allow to dry. Protect eyes and skin by wearing protective equipment including rubber gloves and eye goggles when working with bleach solution.

Application and Clean-up

Paint only when surface and air temperatures are above 50 °F (10 °C). Stir paint thoroughly before and while painting. Do not apply late in the day or when dew or rain is likely. Moisture or high humidity will adversely affect adhesion of paint film. Start painting at the highest point and work from left to right. Paint the gutters and downspouts and then the windows and frames. To prevent sticking, move windows up and down after four hours. Next, do the siding. Brush paint well into the surface. Always finish up at a door, window or outer edge. Do not stop painting in the middle of an empty space. Do not thin. Clean tools and equipment with paint thinner.

Cautions (18-2121-11 Series)

WARNING: CONTAINS PETROLEUM DISTILLATE AND CRYSTALLINE SILICA. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose, and throat irritation. USE ONLY WITH ADEQUATE VENTILATION. Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's direction for respirator use. AVOID CONTACT WITH EYES AND SKIN. Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the state of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. **Cancer hazard:** Contains crystalline silica which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 380 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

PDS 18-2121

valspar

1191 Wheeling Rd, Wheeling, IL 60090 800-845-9061
www.valspar.com

12/09