

True Basics® by Valspar® Exterior Latex Flat Paint

No. 24550 Series

GENERAL DESCRIPTION

True Basics® by Valspar® provides a durable, beautiful finish that resists the effects of the harshest weather. It provides a beautiful finish that resists chalking, fading and yellowing.

PRODUCT FEATURES

- Good adhesion & coverage
- Resists fading
- Durable formula
- Self-priming

RECOMMENDED USES

Properly prepared exterior wood and metal siding and trim including hardboard, fiber cement board, vinyl, primed metal, shakes, brick, cement, cinder block and stucco. Do not use on glazed brick, floors or steps.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Quart – 4 per carton
- Gallon – 4 per carton

COMPOSITION

Base and Fill Levels

(oz./gal.)

White (24550)	128
Pastel Base (24551)	126
Tint Base (24552)	124
Clear Base (24553)	116

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Start at the highest point of the house and work across. Always paint back into freshly painted areas and end up at a door, window or outer edge. Move windows after 1 hour to prevent sticking.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.017–0.021"

Brush: premium-quality polyester brush

Roller: premium quality polyester 3/8–1/2" nap

SYSTEM

RECOMMENDATIONS

New Wood:

Prime with True Basics® Exterior Latex Flat

2 Coats: True Basics® Exterior Latex Flat

Previously Painted Surfaces:

Prime with True Basics® Exterior Latex Flat

1–2 Coats: True Basics® Exterior Latex Flat

Hardboard Siding:

Prime with True Basics® Exterior Latex Flat

1–2 Coats: True Basics® Exterior Latex Flat

Masonry, Concrete, Stucco, and Block:

Prime with True Basics® Exterior Latex Flat

1–2 Coats: True Basics® Exterior Latex Flat

Metal:

Prime with Valspar® Armor Anti-Rust Primer

1–2 Coats: True Basics® Exterior Latex Flat

Aluminum and Vinyl Siding:

Prime with True Basics® Exterior Latex Flat

1–2 Coats: True Basics® Exterior Latex Flat

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acrylic Copolymer

Pigment Type: Titanium dioxide

Viscosity: 95–103 Krebs Units

Gloss: 0–5 Units @ 60° angle

Flashpoint: N/A

VOC (g/L): less than 50 g/L

Volume Solids: 32%

Weight Solids: 47%

Weight Per Gallon: 10.9 lbs./gal

Practical Coverage: Covers approximately 300–400 sq. ft. per gallon (27–37 m² per 3.78 L) depending on surface porosity. Do not thin.

Recommended Film Thickness:

3.5 mil Wet 1.3 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 1 hour

Recoat: 4 hours

Application Temperature: 50–90 °F (10–32 °C)

*Data reported is typical of White and will vary by color and batch.

REGULATORY COMPLIANCE

Current as of: 7/17/2019

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

True Basics® by Valspar® Exterior Latex Flat Paint

No. 24550 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew.

Clean mildew from the surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

Previously painted surfaces (including painted metal siding):

Scrape off loose and peeling paint, sand smooth, then spot prime. Thoroughly remove chalk by vigorous washing, then rinse. Remove gloss from shiny surfaces. Countersink nails and apply an oil-based metal primer to exposed nail heads. Caulk cracks and joints.

Bare wood: For maximum performance, 2 coats of True Basics® by Valspar® are recommended.

Vinyl siding: Wash thoroughly and allow to dry. Paint with a color lighter than original siding color. **WARNING** — Painting with darker colors will cause warping or deformation from heat absorption.

Hardboard siding (unprimed, primed or previously painted): Remove any wax from bleed-through areas by wiping with rags soaked with mineral spirits. Turn rags often to avoid merely spreading wax around.

Masonry:

Brush loose sand, dust and other material from the surface.

Metal:

New galvanized surfaces should be allowed to age 6 months before painting.

New Fiber Cement Board:

Wash thoroughly and allow to dry.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to perform to your satisfaction at the time of application when applied to a properly prepared residential surface in accordance with the label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights that vary from state to state.

CAUTIONS

CAUTIONS Use only with adequate ventilation. To avoid overexposure, open windows and doors to use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. SEE MATERIAL SAFETY DATA SHEET.**

UCL 3.1

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

Valspar, Cleveland, Ohio 44115
Revised: 7/17/19