Safety Data Sheet

* Trusted Quality Since 1921 *

www.rustoleum.com

1. Identification					
Product Name:	GARDZ QT 6PK	Revision Date:	5/14/2015		
Product Identifier:	2304	Supercedes Date:	5/6/2015		
Product Use/Class:	Primer/Waterbased GARDZ				
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA		
Preparer:	Regulatory Department				
Emergency Telephone:	hergency Telephone: 24 Hour Hotline: 847-367-7700				

2. Hazard Identification

EMERGENCY OVERVIEW: Use ventilation necessary to keep exposures below recommended exposure limits, if any. May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN. Harmful if inhaled. Causes eye irritation.

Classification

Symbol(s) of Product



Signal Word Warning

GHS HAZARD STATEMENTS

GHS HAZARD STATEMENTS			
Acute Toxicity, Dermal, category 5	H313	May be harmful in contact with skin.	
Skin Irritation, category 2	H315	Causes skin irritation.	
Aspiration Hazard, category 2	H305	May be harmful if swallowed and enters airways	
Skin Irritation, category 3	H316	Causes mild skin irritation	
Eye Irritation, category 2B	H320	Causes eye irritation	
GHS LABEL PRECAUTIONARY STATE	MENTS		
P102	Keep out of	reach of children.	
P103	Read label I	before use.	
P202	Do not hand	le until all safety precautions have been read and understood.	
P234	Keep only in original container.		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P262	Do not get in eyes, on skin, or on clothing.		
P264	Wash thor	roughly after handling.	
P271	Use only ou	tdoors or in a well-ventilated area.	
P273	Avoid release to the environment.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P281	Use personal protective equipment as required.		
P285	In case of in	adequate ventilation wear respiratory protection.	

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P335	Brush off loose particles from skin.
P350	Gently wash with plenty of soap and water.
P351	Rinse cautiously with water for several minutes.
P374	Fight fire with normal precautions from a reasonable distance.
P402	Store in a dry place.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P362	Take off contaminated clothing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P332+P313	If skin irritation occurs: Get medical advice/attention.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	<u>Wt.%</u> Range	GHS Symbols	GHS Statements
Propylene Glycol Monobutyl Ether	5131-66-8	2.5-10	GHS02-GHS07	H226-302-315-319

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted. Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Avoid contact with eyes. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. **STORAGE:** Keep from freezing. Keep container closed when not in use. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Page 3 / 5

8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Propylene Glycol Monobutyl Ether	5131-66-8	5.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Relative Density:	1.012	pH:	N.D.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/	N.a. Information
Decompostion Temp., °C:	No Information	water:	No Information
Boiling Range, °C:	88 - 350	Explosive Limits, vol%:	0.9 - 7.0
Flammability:	Does not Support Combustion	Flash Point, °C:	59
Evaporation Rate:	Slower than Ether	Auto-ignition Temp., °C:	No Information
Vapor Density:	Heavier than Air	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: Low hazard for usual industrial handling or commercial handling by trained personnel. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

Chemical Name	CAS-No.
5-Chloro-2-Methyl-4-Isothiazolin-3-one	26172-55-4
Methyl-4-Isothiazolin-3-one	2682-20-4

CALIFORNIA PROPOSITION 65:

WARNING: This product contains a substance known to the State of California to cause cancer.

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

WARNING: This product contains a substance known to the State of California to cause birth defects or other reproductive harm.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations:

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

16. Oth	ner Inf	ormation					
HMIS RA							
Health:	2	Flammability:	1	Physical Hazard:	0	Personal Protection:	Х
CANADIA		MIS CLASS:	D2B				
NFPA RA	TINGS						
Health:	2	Flammability:	1	Instability	0		
VOLATILE	ORGA	NIC COMPOUN	DS, g/L:	96			
MSDS REV	VISION	DATE:	5/14/2015				
REASON F	FOR RE	EVISION:	No Information				
Legend: N.	A No	t Applicable, N.E	Not Establishe	d, N.D Not Determin	ed		

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.