



**SKID TEX  
ST30 NON-SKID ADDITIVE**

**DESCRIPTION AND USES**

Skid Tex is an extremely fine mineral compound that when added to paint will provide a durable, non-skid finish in all types of floor paints. Skid Tex can be used in interior and exterior paints to help prevent slips and falls. Skid Tex will not change color or the performance properties of the paint.

**PERFORMANCE CHARACTERISTICS**

- Easy to use non-skid additive for paint
- Helps prevent slips and falls
- Can be used in interior and exterior floor paints

**PRODUCTS**

SKU	Description
22242	1-Pound Package

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Follow paint manufacturer's directions for surface preparation.

**PRODUCT APPLICATION (cont.)**

**INSTRUCTIONS FOR USE**

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. In a clean, separate container, add Skid Tex to the paint, in a proportion of one pound to one gallon of paint. Add ½ cup of Skid Tex for one quart of paint. Mix thoroughly using a slotted paint paddle or mechanical agitator to ensure the additive is incorporated. Let the mixture sit for at least 30 minutes before applying. Stir occasionally to ensure good distribution of the mixture. Use a ¾" to ¾" nap roller and follow the manufacturer's directions for paint application. If two coats of paint are used, Skid Tex may be used in both coats. For high gloss finishes, use Skid Tex in the first coat only then apply a high gloss topcoat.

**CLEAN-UP**

Follow paint manufacturer's directions for clean up and disposal.

**PHYSICAL PROPERTIES**

		CONCRETE ETCH
<b>Composition</b>		Pumice, Crystalline Silica
<b>Weight</b>	<b>Per Gallon</b>	20.3 lbs.
	<b>Per Liter</b>	2.43 kg
<b>Solids</b>	<b>By Weight</b>	100%
<b>Volatile Organic Compounds</b>		0 g/l
<b>Practical Coverage</b>		Will depend on the method of application and surface type
<b>Shelf Life</b>		5 years
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.